


# PU High Build Transparent Basecoat

Written by Administrator  
Friday, 24 August 2012 06:34 - Last Updated Tuesday, 23 October 2012 06:31





**SAYERLACK**  
INNOVATIVE WOOD SOLUTIONS

Sayerlack is a brand of  
Sayer-Wood

SAYERLACK S.r.l. with a legal representative  
Sayer-Wood S.r.l. (Sayer-Wood S.p.A. Italy) 20137  
Via Sayerlack 1 - 20137 Milano (Italy)  
Tel. +39 02 57400000 - Fax +39 02 57400001  
E-mail: [info@sayerlack.it](mailto:info@sayerlack.it)  
Website: [www.sayerlack.it](http://www.sayerlack.it)

[CLICK TO ENLARGE](#)

**Technical Data Sheet**

**TU014200**  
CLEAR POLYURETHANE BASECOAT - HIGH-BUILD

two-component paint

self-priming

Area of use:	Flat, parts, roof, furniture, wood, parts, doors
Method of use:	Spraygun and brush roller
Mixing procedure:	by weight (kg) by volume (l)
Part A	TU014200 100 100
Part B (hardener)	TD077500 50 50
Thinner	DT115000 15-30 15-40

Technical characteristics:

Solids content (%)	Part A: 48 ± 1 Part B: 28 ± 1
Specific gravity (kg/l)	Part A: 0.980 ± 0.005 Part B: 0.940 ± 0.020
Viscosity (DIN 4 at 20°C)	Part A: 200 ± 50 A + B: 200 ± 50
Flashpoint	3°C min
Recommended application weight (kg/m²)	Min. 80 - Max. 300
Interval between coats	Min. 40 - Max. 5 hours
Number of coats	Max. 4