



Vinyl Sealer/ Stopper

Written by Administrator
Friday, 24 Aug 2012 07:22 - Last Updated Tuesday, 23 October 2012 07:41





Product Finishes

VINYL SEALER

LOW VOC FORMULA

CLICK TO ENLARGE

DESCRIPTION	CHARACTERISTICS	RECOMMENDATIONS
<p>It is designed for use on all types of masonry surfaces to provide a protective barrier against water penetration and staining. It is also suitable for use on concrete, brick, stone, and other masonry surfaces.</p> <p>Application:</p> <ul style="list-style-type: none">Apply with brush or roller.Apply in thin coats.Allow each coat to dry before applying the next.Apply to clean, dry, and sound surfaces.Apply to all surfaces to be protected. <p>Notes:</p> <ul style="list-style-type: none">For best results, apply to clean, dry, and sound surfaces.For more information, see the product literature.	<p>Properties:</p> <ul style="list-style-type: none">It is a clear, water-based product.It is suitable for use on all types of masonry surfaces.It is also suitable for use on concrete, brick, stone, and other masonry surfaces. <p>Technical Data:</p> <ul style="list-style-type: none">Viscosity: 100-150 cP (at 25°C)Density: 1.05 g/cm³ (at 25°C)Specific Gravity: 1.05 (at 25°C)Flash Point: 100°C (212°F)Boiling Point: 150°C (302°F)Freezing Point: -10°C (14°F) <p>Storage:</p> <ul style="list-style-type: none">Store in a cool, dry place.Protect from frost.Do not use if the product has become lumpy or has a strong odor. <p>Package Size: 2.5 gallons (9.5 liters)</p>	<p>Notes:</p> <ul style="list-style-type: none">Apply to clean, dry, and sound surfaces.For best results, apply to clean, dry, and sound surfaces.For more information, see the product literature.