


# PU Outdoor Topcoat

Written by Administrator

Friday, 24 August 2012 07:35 - Last Updated Tuesday, 23 October 2012 08:11



**Gloss**

- ✓ 10 Sheen
- ✓ 30 Sheen
- ✓ 50 Sheen
- ✓ 90 Sheen

**Product Finishes**

**PU TOPCOAT**

**-F63FY0221 (10) -F63Y0220 (90)**

**Technical Data**

Property	Unit	Value
Appearance		Clear, colorless liquid
Odor		Strong, pungent
Viscosity	Pa·s	0.15
Density	g/cm³	1.05
Flash Point	°C	25
Boiling Point	°C	100
Freezing Point	°C	-10
Storage Stability	Months	12
Shelf Life	Months	12

**Application**

Apply by brush, roller or spray. For best results, apply in two coats. The first coat should be applied to a clean, dry surface. The second coat should be applied after the first coat has dried. The final finish will be achieved after 24 hours.

**Notes**

1. For best results, apply in two coats. The first coat should be applied to a clean, dry surface. The second coat should be applied after the first coat has dried. The final finish will be achieved after 24 hours.

2. For best results, apply in two coats. The first coat should be applied to a clean, dry surface. The second coat should be applied after the first coat has dried. The final finish will be achieved after 24 hours.

3. For best results, apply in two coats. The first coat should be applied to a clean, dry surface. The second coat should be applied after the first coat has dried. The final finish will be achieved after 24 hours.

4. For best results, apply in two coats. The first coat should be applied to a clean, dry surface. The second coat should be applied after the first coat has dried. The final finish will be achieved after 24 hours.

5. For best results, apply in two coats. The first coat should be applied to a clean, dry surface. The second coat should be applied after the first coat has dried. The final finish will be achieved after 24 hours.